



SPECIFICATION SHEET

Fall Protection

Lanyard with Tubular Style Energy Absorber - One 2.2" Hook and One Standard Hook, Class B (CCK618)

Product #	Colour	Length
CCK618	Yellow	6' (1,8m)

Description


- 1" lanyard with nylon core and polyester tubular sheath
- Inner energy absorber
- Zinc-plated steel carabiners with double lock and 3/4" (19 mm) opening resist to a maximum force of 17 kN (3,600 lb.)
- 2.2" self-locking hook made of galvanized steel for scaffolding
- Impact indicator
- Peak arrest force: 408 kg (900 lb.)
- Maximum fall distance: 1.8m (6')
- Maximum deployment: 1.2m (4')
- Worker weight with tools: 66kg (145lb) - 140kg (310lb)
- CSA Z259.11-17 and ANSI Z359.13 certified



*Deceleration Distance Per User Weight (Based on 6' Free Fall)	
Weight	Deceleration
130 lbs / 60 kg	13" / .33 m
154 lbs / 70 kg	15" / .39 m
176 lbs / 80 kg	19" / .47 m
198 lbs / 90 kg	21" / .54 m
220 lbs / 100 kg	24" / .62 m
242 lbs / 110 kg	28" / .71 m
265 lbs / 120 kg	32" / .80 m
286 lbs / 130 kg	35" / .90 m
310 lbs / 140 kg	40" / 1.01 m

Must use 48" maximum in fall clearance calculation, unless calculation is done by Qualified Person.

Key Features :

 Z259.11-17 Class B	Worker's weight Minimum 66kg (145 lb.) Maximum 140kg (310 lb.)	Tubular Style Energy Absorber
--	---	--

PROTECTION • RELIABILITY • VALUE