

### Lanyard with Pack-Style Energy Absorber - 2 Standard Hooks, Class B (CCK420 - CCK620)



Product #	Colour	Length
CCK420	Yellow	4' (1,2m)
CCK620	Yellow	6' (1,8m)

#### Description


- 1" polyester lanyard
- Pack-style energy absorber
- Two zinc-plated steel carabiners with double lock and 3/4" (19 mm) opening resist to a maximum force of 17 kN (3,600 lb.)
- Peak arrest force: 408 kg (900 lb.)
- Maximum fall distance: 1.8m (6 ')
- Maximum deployment: 1.2m (4 ')
- Worker weight with tools: 60kg (130lb) - 140kg (310lb)
- CSA Z259.11-17 and ANSI Z359.13 certified
- Class B

#### \*Deceleration Distance Per User Weight (Based on 6' Free Fall)

Weight	Deceleration
130 lbs / 60 kg	13" / .33 m
154 lbs / 70 kg	15" / .39 m
176 lbs / 80 kg	19" / .47 m
198 lbs / 90 kg	21" / .54 m
220 lbs / 100 kg	24" / .62 m
242 lbs / 110 kg	28" / .71 m
265 lbs / 120 kg	32" / .80 m
286 lbs / 130 kg	35" / .90 m
310 lbs / 140 kg	40" / 1.01 m

Must use 48" maximum in fall clearance calculation, unless calculation is done by Qualified Person.

#### Key Features :

 <b>Z259.11-17</b> <b>Class B</b>	<b>Worker's weight</b> <b>Minimum 60kg (130 lb.)</b> <b>Maximum 140kg (310 lb.)</b>	<b>Pack-Style Energy</b> <b>Absorber</b>
--	---	---

**PROTECTION • RELIABILITY • VALUE**