

V-SERIES™ Standard & Leading-Edge SRLs

Technical Data Sheet



V-TEC™ Standard SRL

CAPACITY ANSI Z359.14 CLASS B CSA Z259.2.2	130–310 lb. (59–140 kg)
	130–310 lb. (59–140 kg)
BRAND	MSA
MODEL NAME	V-TEC
LENGTHS	20 ft. (6 m)
	30 ft. (10 m)
	50 ft. (15 m)
	100 ft. (30 m)
WEIGHTS	20 ft. (6 m) — 7 lb.
	30 ft. (10 m) — 15.7 lb.
	50 ft. (15 m) — 16.1 lb.
	100 ft. (30 m) — 37 lb.
CONNECTOR OPTIONS	Steel swivel snaphook
HOUSING MATERIAL	Clear polycarbonate; aluminum housing for 100 ft. lengths
HARDWARE MATERIALS	Steel, stainless steel
LIFELINE MATERIALS	3/16" (5 mm) galvanized steel cable or 3/16" (5 mm) stainless steel cable
ENERGY-ABSORBING TECHNOLOGY	Patented tolerance ring energy absorber
ARREST FORCES	
	PEAK 1,800 lb. (8 kN) AVERAGE 900 lb. (4 kN)
KEY FEATURES	Retraction brake
	Stowable carry handle
	Clear inspectable housing
PRODUCT STYLES	Standard SRL
PRODUCT TYPES	Construction
	OGP
	General industry
STANDARDS	ANSI Z359.14 Class B
	CSA Z259.2.2
	EN360:2002
	OSHA

V-TEC Standard SRL
30 ft. (10 m) / 50 ft. (15 m)



V-TEC Standard SRL
100 ft. (30 m)

WE KNOW WHAT'S AT STAKE.

V-EDGE™ Leading-Edge SRL

CAPACITY	
ANSI Z359.14 CLASS LE	130–310 lb. (59–140 kg)
CSA Z259.2.2 SRL-LE	130–310 lb. (59–140 kg)
BRAND	MSA
MODEL NAME	V-EDGE
LENGTHS	20 ft. (6 m) 30 ft. (10 m) 50 ft. (15 m)
CONNECTOR OPTIONS	Steel swivel snaphook
HOUSING MATERIAL	Clear polycarbonate
HARDWARE MATERIALS	Steel
LIFELINE MATERIALS	3/8" (5 mm) galvanized steel cable
ENERGY-ABSORBING TECHNOLOGY	Tear webbing with protective case
KEY FEATURES	Retraction brake Leading-edge roll cage Hard-cased external energy absorber Clear inspectable housing
PRODUCT STYLES	Leading-edge SRL
PRODUCT TYPES	Construction OGP General industry
STANDARDS	ANSI Z359.14 Class LE CSA Z259.2.2 SRL-LE EN360:2002 OSHA



Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit [MSAafety.com/offices](https://www.MSAafety.com/offices).