

SPECIFICATION SHEET

Fall protection



KOSTO
BUILT STRONG • BÂTI SOLIDE

3-Way 66' Retractable Lifeline for Rescue / Retrieval SRL-R with Indicating Carabiner

CDK350

66' (20m)

This 3-way **66-foot self-retractable lifeline** is engineered for maximum safety and versatility in rescue operations and work at height. Combining fall arrest and emergency rescue in one robust unit, it features a durable 20m (66') galvanized steel cable for reliable performance in critical situations.

The ergonomic recovery system enables quick deployment, and an additional handle makes transport effortless. Designed with safety in mind, this SRL-R meets rigorous industry standards to protect users in hazardous environments. A swivel aluminum carabiner helps prevent accidental disengagement, while the lightweight Aluminium housing shields internal components without adding bulk.

Certification

Certified

- ⇒ **CSA Z259.2.2-17(R2022), Class SRL-R**
Meets and Exceeds
- ⇒ **OSHA 29 CFR1910.66/1926.502**
- ⇒ **ANSI Z359.14-2021, Class 1**



Mounting point for support installation on tripod (CTK910 sold separately)

Must be mounted only on the **upper leg** of the tripod.



Compatible with Tripod CTK012; SRL and bracket are **included** in the **CTK012 kit**

Ensure the anchor point is positioned above the user's dorsal D-ring for optimal safety. During fall arrest, the lifeline must remain clear of any edges to prevent damage and ensure reliable performance



Connection point rotates 360 degrees to ensure that the unit remains in the best orientation

Aluminum housing

Ergonomic carrying handle

Ergonomic handle for recovery system; lift the handle to a 180-degree vertical position to activate recovery mode

Bumper, to protect the spring from unguided retraction.

3/16", 5mm / Galvanized steel cable

Double action, swivel, indicating carabiner with 3/4" opening, designed for secure connection to harness D-Ring



- Maximum arresting distance: 1.2m (47")
- Average arresting force: 6kN, 1350lbs
- Maximum arresting force: 8kN, 1800lbs
- Maximum free fall: 0.6m (2')
- **Net weight:** 14 kg (30.8 lb)

Capacity:

59-141kg (130-310lbs) (weight range including equipment)

Technical Data

Material

Cable	3/16", 5mm Galvanized steel
Housing	Aluminum
Carabiner	Aluminum
Energy absorber	Polyester tear-away

Switching from SRL Mode to Winch Mode:



1 Ensure the device is currently in SRL mode.



2 Pull the button to disengage the winch lock.



3 Push the handle bar to engage the winch mode. It may require a slight turn so that the internal teeth nest together.



4 Make sure both buttons are fully engaged in Winch Mode.



SPECIFICATION SHEET

Fall protection



KOSTO
BUILT STRONG • BĀTI SOLIDE

Associate Products

Covers the ABCD of fall protection: Anchor points, Body support (harnesses), Connecting devices (lanyards) - Descent and Rescue ensuring complete safety at height.

Descent and Rescue

Tripod Kit CTK012



Winch CTK165



Support CTK910 for CDK350 and CTK165



Harness CHK131



Harness XPRO CHK230



Connecting elements

Lanyards CLK



Self-Retracting Lifeline CDK



Anchor CAK



Maintenance and Inspection

Maintenance

- Clean after each use to maintain safety and durability.
- Remove any dust, corrosive material or contaminants.
- If the fall protection system cannot be cleaned with clean water, use mild soap and water, then rinse and wipe dry.
- NEVER clean the fall protection system with corrosive materials.
- Hang to dry in a cool dry place and store in a bag when completely dry


Inspection

- Before EVERY use, inspect the fall protection system for defects.
- IMMEDIATELY remove the fall protection system from service if any defects or damage are found, or if it is exposed to fall arrest forces.
- At least every 12 months, a competent person other than the user shall inspect the lanyard.

Important

- Always follow the manufacturer's instructions provided with this SRL.
- Carefully read and fully understand all instructions before using the product.
- Improper use of this equipment can result in serious injury or death.
- Avoid contact with sharp edges or abrasive surfaces that could cut or damage its components.
- Ensure all connections are secure, compatible, and safe.
- Use only with other CSA- or OH&S-compliant equipment as part of a complete fall protection system.
- Immediately remove this device from service if it has been involved in a fall.

Refer to instruction manual



CDK350
See Instructions