

Leading Edge Self Retracting Lifeline 65' (CDKL65)



Can be used in 2 ways:

Overhead use: (Non-LE)

- CSA Z2592.2-17 Class SRL and ANSI Z359.14 Class B
- Maximum arresting distance: 47" (1.2m)
- Minimum fall clearance: 7.4' (2,3m)
- Free fall not permitted

Key Features :

Product #	Cable	Length
CDKL65	Galvanized steel 3/16"	19.8m (65')

Material






- 19.8m (65') galvanized cable
- Aluminum housing and stainless steel components

Confection

- Self-retracting device 65' long for Leading Edge
- Anchor point carabiner with swivel snap hook
- Zinc-plated steel carabiners with double lock and 3/4" (19 mm) opening resist to a maximum force of 17 kN (3,600 lb.)
- Capacity: CSA: 45kg (100lb) -140kg (310lb) and ANSI: 130-310 lbs. (59-140 kg)
- Average arresting force: 4.4 kN (900 lbs) and Maximum arresting force: 8kN (1800lb)

Use for leading edge (LE) / with free fall:

- CSA Z2592.2-17 Class SRL-LE and ANSI Z359.14 Class SRL-LE
- Min. setback distance from edge: 0'
- Maximum arresting distance: 102" (2.6 m)
- Minimum fall clearance: 18' (5.5 m)
- Max. free fall: 6 '(1.8 m)

 <p>Z259.2.2-17 Class SRL</p>		<p>Galvanized steel cable With energy absorber</p> 	<p>Tag line included</p> 	<p>Ergonomic handle for Transport</p> 
---	---	--	--	---