

# SPECIFICATIONS SHEET

## Fall protection



# KOSTO

BUILT STRONG • BĀTI SOLIDE

## Construction Harness– 3 Rings, Class AP

### CHK014

This 6-point adjustable construction harness offers enhanced comfort when working at height, thanks to removable cushioned padding at the shoulders, and the waist belt provides excellent, comfortable lumbar support. Class AP, it features 3 D-rings, one on the back and two on the sides for positioning. Ideal for construction sites and many types of work requiring a restraint system.

#### Certification

- **CSA Z259.10 class AP** certified
- **ANSI Z359.1**

#### Material


100% polyester for increased resistance to chemicals  
Galvanized steel

#### Size:

Universal

#### Capacity

160kg (352lbs)



# SPECIFICATIONS SHEET

## Fall Protection



**KOSTO**  
BUILT STRONG • BĀTI SOLIDE

### Associate Products

Harness **CHK001**



Harness **CHK214**



#### Connecting elements

Lanyards CCK



Self-Retracting Lifeline CDK



D-ring Extension **CCK008/CCK018**



Anti-Trauma Safety Strap **CSK001**



Tool Lanyard **CAK050**



Carrying Bag **K-BAG**



Fall Arrest Class A



Retrieval Class E



Fall Arrest Class A



Retrieval Class E



positioning Class P



### Maintenance and Inspection

#### Maintenance

Clean after each use to maintain safety and durability. Remove any dust, corrosive material or contaminants. If the fall protection system cannot be cleaned with clean water, use mild soap and water, then rinse and wipe dry. NEVER clean the fall protection system with corrosive materials.

#### Inspection

Before EVERY use, inspect the fall protection system for defects.

IMMEDIATELY remove the fall protection system from service if any defects or damage are found, or if it is exposed to fall arrest forces.

At least every 12 months, a competent person other than the user should inspect the harness.

### Sizing Chart

