

SPECIFICATION SHEET

Fall protection



KOSTO
BUILT STRONG • BĂȚI SOLIDE

X-PRO General Harness with Quick-Connect - 4 D-Rings, Class ALP

CHK328

This **Kosto 5-point adjustable safety harness** is made from 100% polyester, offering superior resistance to chemicals and wear. Designed for optimal performance at height, it features **lightweight aluminum D-rings** - including a **dorsal D-ring**, a **front D-ring** for attachment to vertical ladder climbing systems, and **two lateral D-rings** for secure and precise worker positioning. The use of **aluminum** makes the harness lighter, enhancing comfort without compromising safety.

Trauma suspension straps are integrated, providing a complete, and ready-to-use fall protection system. Classified as **Class ALP**, this harness combines enhanced comfort with reliable safety, making it an ideal choice for a wide range of professional applications. For added comfort, it features **breathable padding** with a honeycomb structure at the shoulders, and thighs, ensuring optimal airflow and reducing heat buildup during extended use.

Certification

- **CSA Z259.10-18, Class ALP** certified
- Meets and exceeds:
 - ⇒ **ANSI Z359.11-2021, ANSI A10.32-23**
 - ⇒ **OSHA 1910, OSHA 1926 Subpart M**

Aluminum back D-ring

Dual SRL slot

X in PVC to prevent tangling and slippage

Impact indicator

Labels protector cover with Instruction manual QR code



Integrated trauma straps

Seat strap for more comfort

Comfortable ventilated padding featuring honeycomb structure for enhanced breathability

Resettable Lanyard keeper

5 adjustment points
⇒ 2 x legs,
⇒ 2 x body,
⇒ 1 x chest

Chest quick-connect for fast and secure donning, with front D-Ring that can be attached to vertical ladder climbing systems.



Webbing Adjuster

2x lateral D-rings for worker positioning

Quick connect at legs for a secure and customizable fit

Comfortable ventilated pads



Fall arrest
Class A



Ladder
Class L



Positioning
Class P



PROTECTION • RELIABILITY • VALUE

WWW.SPI.COM

SPECIFICATION SHEET

Fall protection



KOSTO
BUILT STRONG • BÂTI SOLIDE

Associate Products

Covers the ABC of fall protection: Anchor points, Body support (harnesses), Connecting devices (lanyards) - ensuring complete safety at height.

Harness
CHK135



Harness XPRO
CHK238



Connecting elements

Lanyards CLK



Self-Retracting Lifeline
CDK



Anchor
CAK



Tool Lanyard
CAK030



Carrying Bag
XKW030



D-ring Extension
CCK118



Maintenance and Inspection


Maintenance

- Clean after each use to maintain safety and durability.
- Remove any dust, corrosive material or contaminants.
- If the fall protection system cannot be cleaned with clean water, use mild soap and water, then rinse and wipe dry.
- NEVER clean the fall protection system with corrosive materials.
- Hang to dry in a cool dry place and store in a bag when completely dry


Inspection

- Before EVERY use, inspect the fall protection system for defects.
- IMMEDIATELY remove the fall protection system from service if any defects or damage are found, or if it is exposed to fall arrest forces.
- At least every 12 months, a competent person other than the user shall inspect the harness.

Sizing Chart



For all applications: work weight capacity range (including all clothing, tools, and equipment) is 130-310lbs.



CHK23
See Instructions