



50' Rescue and Retrieval System for Confined Spaces (CTK002)



Dimensions

	Minimum height inch (mm)	Maximum height inch (mm)
Storage	64 (1626)	----
Hole diameter	34 (864)	57 (1448)
Overall height	58 (1473)	90 (2286)
Available lift height	38 (965)	70 (1778)
Height increments	2 (51)	---
Spread of legs inside the shoe	46 (1168)	72 (1829)

Key Features :

Mounting bracket 	Rated for one worker, or two workers <u>during assisted rescue only</u>. Each worker must attach to a separate connection point (maximum combined worker capacity is 620 lbs)	SRLs lightweight type 3 with a 6.3:1 recuperation crank ratio and a 50 feet of travelling allowance.	Rescue winch <u>option available</u> : CTK060 
--	--	---	---

Product #	Cable	Length
CTK002	Galvanized steel 3/16"	15.2m (50')

Material

- 7' (2.1m) aluminum tripod
- 3/16" wide 50' galvanized steel 3-way SRL
- Stainless steel, aluminum, polyethylene and neoprene components

Confection

- 1 tripod with safety chain
- 3-way self-retracting lifeline, 50' galvanized steel cable
- Adjustable legs
- Average speed rate of 4.5ft / sec
- Max fall arrest forces: 1,800lbs or less
- Robust and practical transport bag
- Capacity: 58.96kg (130lb.) - 140kg (310lb.) (equipment included)
- Compliant with CSA Z259.15-2017, OSHA 1910, OSHA 1926 Subpart M, ANSI A10.32-2012, ANSI Z359.18-2017