



# ANTI-VIBRATION CUT LEVEL 4 HIGH-DEXTERITY NITRILE DIPPED GLOVE

## BEST VIBRATION PROTECTION.\* HIGH DEXTERITY.

ISO 10819 | TRM=0.67 | TRH=0.52

**ANTI-VIBRATION**

**CUT LEVEL 4**

ANSI/ISEA 105



**SMARTWIPE™ Touch  
Screen Compatible  
Fingertips**

**Best Vibration  
Reduction\***

**Long-Lasting  
Nitrile Dip**

\*Compared to knit and dip anti-vibration gloves when measuring transmission of the ISO 10819 vibration profile to the palm and fingers



**18 Gauge Knit  
Total Mobility**

**TPR Knuckle  
Protection**

**Light & Breathable  
Design**

**Reinforced Nitrile Coating  
Between thumb  
and forefinger**

### EN388 STANDARDS

Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	2	4	5	X**
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

\*\*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead



SPECIFICATIONS		RECOMMENDED APPLICATIONS	CARE INSTRUCTIONS
Gauge	18	<ul style="list-style-type: none"> <li>Demolition</li> <li>Material Handling</li> <li>High Dexterity Applications</li> <li>General Work</li> <li>Automotive</li> <li>Remodeling</li> <li>Carpentry</li> <li>Tree Care</li> </ul>	Machine wash warm water (105°F), mild detergent, no bleach. Line dry.
Liner Material	HPPE Blend Knit		
Dip Material	Sandy Nitrile		
Cuff Style	Elasticated Knit		

SIZE	1 PAIR
S	48-73-8760
M	48-73-8761
L	48-73-8762
XL	48-73-8763
XXL	48-73-8764

**SEE  
MORE  
PPE**



or visit <https://qr.mke.tl/2r2xz>

