

SHOWA  
**381**



381 provides the lightest SHOWA microporous nitrile coated glove with an abrasion resistance up to level 4. It's design and comfort is further enhanced as breathability and moisture evacuation by 20% more than our standard offering.

**[ FEATURES**

- Embossed microporous nitrile palm finish
- SHOWA engineered microfiber yarns (0.52 denier)
- High abrasion resistance level 4
- Ultra-light weight: 19 g
- Palm Thickness : 0.90mm
- Excellent fitting due to optimal liner design
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand

**[ BENEFITS**

- Abrasion resistance lasts twice as long as SHOWA 380 (8000 cycles vs 4000)
- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments
- The 0.84mm finger thickness provides an excellent level of tactility and sensitivity
- Microfibre properties boost vapour permeation and enhances breathability thus drier hands and less sweat
- Exceptional suppleness, ultra-comfort and hand fitting thanks to the combination of microfibre and spandex
- A flexible glove designed for easy movement and extended wear
- Seamless knit designed to prevent irritation
- Low lint with microfiber
- No latex allergy risks

**[ INDUSTRY**



Automotive



Construction



Engineering



Municipal Services



Packaging



Warehousing and Distribution

**[ IDEAL APPLICATIONS**

- Public utility
- Police & defense
- Shipping/Receiving



**MATERIAL**

- Microfiber
- Seamless knit

**COATING**

- Foam nitrile

**GRIP**

- Foam

**STANDARDS**

Cat. II



0120

# SHOWA 381



## PACKAGING

- 12 Pair per polybag
- 12 Polybags per case
- 144 Pair per case



## COLOUR

- Grey w/ black palm



## SIZES

- S
- M
- L
- XL
- XXL

## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
306



**MATERIAL**  
Polyester  
**COATING**  
Latex foam

SHOWA  
S-TEX 581



**MATERIAL**  
Kevlar  
**COATING**  
Foam nitrile

SHOWA  
ATLAS® 300



**MATERIAL**  
Cotton  
**COATING**  
Latex

SHOWA  
317



**MATERIAL**  
Polyester  
**COATING**  
Latex

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

**SHOWA USA** | 579 Edison Street - Menlo, GA 30731, USA  
**USA@SHOWAgroup.com**

© SHOWA Group 2018 | All rights reserved