



V4K CONSTRUCTION	STAINLESS STEEL WET	QUARRY TILE DRY	QUARRY TILE WET	QUARRY TILE OIL & WET	Test done by Satra on November 22, 2017 Test method for slip resistance: EN ISO 13287: 2012 (Standard 0.30)
	0.77 0.84	1.09 0.64	0.75 0.46	0.28 0.31	

HARDROCK

S22006-11

Size: 4-14 & 8½-10½

(Women: 2 sizes smaller)

Colour: Black (11)

Height: 10"/25 cm

Width: W



METATECH
SYSTEM 360°

- Waterproof full grain upper with sealed seams.
- Rigid internal METATECH System 360° metguard protection, CSA certified, protects the top as well as the sides of the foot.
- Steel toe protector and composite puncture-resistant insole.
- Breathable and abrasion resistant Cambrelle lining with antimicrobial treatment.
- Waterproof and breathable Sympatex membrane resistant to various pathogens.
- 200 g Thinsulate insulation surrounding the foot.
- Removable Instant Comfort insole made of gel, PU and memory foam.
- 90° heel angle.
- PU scuff resistant bumper toe increasing wear protection.
- Dual density Vibram outsole made of TC4+ natural rubber and a comfortable PU core.
- Fire resistant Nomex thread.
- Padded tongue and collar for added comfort.
- Metal eyelets and speedlaces.
- Nylon shank.
- Norwegian cut.

