

G3 CONSTRUCTION	STAINLESS STEEL WET	QUARRY TILE DRY	QUARRY TILE WET	QUARRY TILE OIL & WET	FROSTED ICE	Test done by Satra on February 24, 2025 Test method for slip resistance: EN ISO 13287: 2019 (Standard 0.30)
	0.67 0.69	0.98 1.03	0.67 0.70	0.31 0.31	0.45 0.51	

G3E A9077B-11

Size: 3-16 & 8½-10½

(Women: 2 sizes smaller)

Colour: Black (11)

Height: 8" / 20.4 cm

Width: WW



Heavy-duty
scratch-proof
Triton Tectuff
leather piece

- 2 mm waterproof full grain leather upper with triple sealed seams with robust Nomex thread.
- Lightweight, non-conductive composite toe with puncture-resistant plate.
- External hard metguard protection with rivets covered with leather.
- Breathable and abrasion resistant Cambrelle lining with antimicrobial treatment.
- Removable insole made of PU offering breathability, comfort and great shock absorption.
- Extra wide fit for more room and comfort.
- Nylon shank.
- PU scuff resistant toe cap for increased wear protection.
- Protective, heavy-duty, scratch-proof Triton Tectuff leather piece, stitched on the inner side of the boot.
- Dual density outsole made of natural rubber and lightweight PU core.
- Natural rubber 4Grip slip resisting outsole, on dry, wet, oily, frosted surfaces; resistant to wear and oil.
- High-visibility reflective inserts
- Absorb+ heel, absorbing shock impacts during impact and increasing grip.
- 90° heel angle.
- Padded tongue and collar for extra comfort.
- Polymer eyelets.



4GRIP

ABSORB+

Cambrelle®

H₂O
Seal

